



1	Identification product code	Steel grade / material no.			
2	Identification of the product	Certificate, delivery note and label			
3	Intended use	Hot-rolled structural steel products for metal building structures or in composite concrete composite structures according to EN 10025-1:2004			
4	Manufacturer	Stahl Gerlafingen AG Postfach CH-4563 Gerlafingen CHE-105.859.757 MWST www.stahl-gerlafingen.com - info@stahl-gerlafingen.com			
5	System to evaluate the performance according to regulation (EU) no. 305/2011	System 2+			
6	Notified body	TUV Rheinland Bautechnik GmbH (0780) Tillystrasse 2 D-90431 Nürnberg			
7	Tasks of the notified body	The notified body has performed the initial inspection of factory and factory production control and the continuous surveillance, assessment and approval of factory production control and has issued the certificate 0780-CPD-52003.			
8	Declared performance	S235 JR/J0/J2	S235/S275 JR/J0/J2	S355 JR/J0/J2	Tolerances on dimensions and shape:  Flat bars in accordance with EN 10058, wide flat bars in accordance with DIN 59200 and angles in accordance with EN 10056-1 and tolerances in accordance with EN 10056-2*  European wide flange beams HEB/IPB and HEA/IPBI in accordance with DIN 1025-2 and -3 and tolerances in accordance with EN 10034  European beams IPE in accordance with DIN 1025-5 and tolerances in accordance with EN 10034  European taper flange channels UPN in accordance with DIN 1026-1 and tolerances in accordance with EN 10279
	Yield strength $R_{eH}$ [MPa]	$\geq 235$ $\geq 225$	$\geq 275$ $\geq 265$	$\geq 355$ $\geq 345$	
	Tensile strength $R_m$ [MPa]	$\geq 360 / \leq 510$ $\geq 26$	$\geq 410 / \leq 510$ $\geq 26$	$\geq 470 / \leq 630$ $\geq 22$	
	Elongation $A_{5,65}$ [%]	$\geq 3 / \leq 40$ $\leq 150$	$\geq 27$ $\geq 27$	$\geq 27$ $\geq 27$	
	Impact strength [J]	Temperature: JR at 20°C / J0 at 0°C / J2 at -20°C $\leq 30$	$\leq 0.40$	$\leq 0.45$	
	Weldability CEV [%]	$> 30 / \leq 40$	$\leq 0.40$	$\leq 0.47$	
	Suitable for zinc coating	Classes 2 and 3			
	Durability	No performance determined			
	Non-radioactivity is controlled.	No performance determined.			
	Regulated material: No performance determined.	No performance determined.			
Electric arc furnace (>95% recycling content). Environmental product declaration ICQM - 14011EPD.	No performance determined.				

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of Stahl Gerlafingen AG by:

*D. Aebli*  
Daniel Aebli  
Chief Operating Officer

*C. Zell*  
Dr. Christoph Zellner  
Head of Quality and Environment